

1- Line Bidirectional ESD Protection Diode

General description

These surge protection diodes are designed for applications requiring transient overvoltage protection capability. They are intended for use in voltage and ESD sensitive equipment such as computers, printers, business machines, communication systems, medical equipment and other applications. These devices are ideal for situations where board space is at a premium.

Features and benefits

- Bidirectional ESD protection of one line
- Reverse stand-off voltage: 24.0V Max
- Low leakage current: nA Level
- Response time is typically < 1 ns
- Low clamping voltage: VC =43V @ IPP = 6 A (TYP)
- ESD Protection: 20kV(air)/ 15kV(contact) (IEC61000-4-2)
- RoHS compliant



Application information

- Cell Phone Handsets and Accessories
- Microprocessor based equipment
- Personal Digital Assistants (PDA's)
- Notebooks, Desktops, and Servers

Ordering information

Device	Package	Packaging	Reel Size
PWESD-24VSDC	SOD323	3000/Tape & Reel	7 Inch

Schematic & Pin configuration

Simplified outline	Graphic symbol
	

Maximum Ratings

($T_{OP} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power ($t_p = 8/20\mu\text{s}$)	P_{PPM}	288	W
Peak Pulse Current ($t_p = 8/20\mu\text{s}$)	I_{PPM}	6	A
ESD voltage IEC 61000-4-2 (air discharge)	V_{ESD}	20	kV
ESD voltage IEC 61000-4-2 (contact discharge)	V_{ESD}	15	kV
Maximum lead temperature for soldering during 10s	T_L	260	$^{\circ}\text{C}$
Storage Temperature Range	T_{stg}	-55 to +150	$^{\circ}\text{C}$
Operating Temperature Range	T_{OP}	-40 to +125	$^{\circ}\text{C}$


Electrical Characteristics

($T_{OP} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Condition
Reverse Working Voltage	V_{RWM}	--	--	24.0	V	
Breakdown Voltage	V_{BR}	26.5	--	31.0	V	$I_T = 1\text{mA}$
Leakage Current I_{Leak}	I_R	--	--	100	nA	$V_{RWM} = 24\text{V}$
Clamping Voltage	V_C	--	32	--	V	$I_{PP} = 1\text{A}, T_p = 8/20\mu\text{s}$
		--	43	48.0		$I_{PP} = 6\text{A}, T_p = 8/20\mu\text{s}$
Junction Capacitance	C_J	--	15	18	pF	$V_R = 0\text{V}, f = 1\text{MHz}$
Junction Capacitance	C_J	--	6.5	8.0	pF	$V_R = 24\text{V}, f = 1\text{MHz}$


Portion Electronics Parameter

Symbol	Parameter
I_{PP}	Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	V_{BR} Test Current




Typical Performance Characteristics


($T_A=25^{\circ}\text{C}$ unless otherwise Specified)




IEC61000-4-2 Pulse Waveform



IEC61000-4-5 8X20 μs Pulse Waveform




Power Derating Curve



Clamping Voltage vs. Peak Pulse Current

Package Outline Dimensions

SOD323



SYMBOL	MILLIMETERS	
	MIN	MAX
A	0.25	0.35
B	1.20	1.40
C	2.40	2.70
H	1.60	1.80
J	0.01	0.15
K	0.70	0.90
L	0.20	0.40
M	0.08	0.15
α	0°	8°

IMPORTANT NOTICE

Wuxi PWChip Semi Technology CO., LTD (PW) reserves the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any products or services. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

PW assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using PW components.

PW products are not authorized for use in safety-critical applications (such as life support devices or systems) where a failure of the PW product would reasonably be expected to affect the safety or effectiveness of that devices or systems.

The information included herein is believed to be accurate and reliable. However, PW assumes no responsibility for its use; nor for any infringement of patents or other rights of third parties which may result from its use.